Epson EB 1930 (V11H506041)
Epson EB-1930, Projectors, Installation, Large Meeting Room, XGA, 1024 x 768, 4:3, 4,200 lumen - 2,730 lumen (economy), 3,000 : 1, USB 2.0 Type B, USB 2.0 Type A, RS-232C, HDMI in, RGB out, Stereo mini jack audio out, RGB in (2x), Stereo mini jack audio in (2x), 10 Base-T, VGA in (2x), VGA out, Composite in, 3.7 kg, 10 W, Computer cable, Power cable, Software (CD), User manual, User manual (CD), Remote control incl. batteries, 36 months On-Site Warranty, Lamp: 12 months

An ideal device for corporate or educational use,the EB-1930 is a great combination of quality output and features at an affordable price.

Key Selling Points

4,200 lumens white/color light output
3LCD technology for vivid colors
Program projector actions in advance
Read PDFs directly from a USB stick

Product Features

Convenient use
The Epson EB-1930 combines high-quality output,value-added features and affordability,into a compact and portable projector. It is perfect for corporate or educational use,as it can be easily installed in meeting rooms or used portably from a desktop.

High quality picture
Utilizing Epson's 3LCD technology to ensure clearly projected images,the EB-1930 produces vivid,natural colors and an equally high white and color light output,even in daylight.

Connectivity
The EB-1930 boasts a DisplayPort connector,allowing you to show high definition audio and video content with ease.

Enhanced productivity
Productivity can be greatly increased with a range of features available with the EB-1930,such as quick corner.

Main Specifications

Product Description	Epson EB 1930 LCD projector
Device Type	LCD projector
Built-in Devices	Speaker
Networking	Ethernet, Fast Ethernet
Brightness	4200 lumens
Contrast Ratio	3000:1
Resolution	XGA (1024 x 768)
Native Aspect Ratio	4:3
Bulb type	215 Watt
Bulb life cycle	Up to 3500 hour(s) / up to 5000 hour(s) (economic mode)
Video Input	RGB, composite video, component video (NTSC, SECAM, PAL, PAL-N, PAL-M, NTSC 4.43, PAL 60) , LAN
Digital Video Standard	High-Definition Multimedia Interface (HDMI)
Video Modes	480p, 720p, 1080i, 1080p, 480i, 720i, 526i, 526p
Video Output	RGB
Speakers	Speaker(s) - integrated
Power	AC 120/ 230 V (50/ 60 Hz)
Power Consumption Operational	298 Watt
Dimensions (WxDxH)	37.7 cm x 10.8 cm x 27.1 cm
Weight	3.7 kg
Manufacturer Warranty	3 years warranty

Extended Specification

General	
Device Type	LCD projector
Built-in Devices	Speaker
Networking	Ethernet
Data Link Protocol	Ethernet,Fast Ethernet
Projector	
Brightness	4200 lumens
Brightness (Reduced)	2730 lumens
Contrast Ratio	3000:1
Image Size	76 cm - 762 cm
Throw Ratio	1.38 - 2.24:1
Resolution	XGA - XGA (1024 x 768)
Native Aspect Ratio	4:3
Display Format	786,432 pixels (1,024 x 768) x 3
Bulb type	215 Watt
Bulb life cycle	Up to 3500 hour(s) / up to 5000 hour(s) (economic mode)
Features	EPSON 3LCD technology
Lens	
Focus Type	Manual
Lens Aperture	F/1.51-1.99
Zoom Type	Manual
Zoom Factor	1.6x
Keystone Correction Direction	Horizontal,vertical
Vertical Keystone Correction	-30 / +30
Horizontal Keystone Correction	-30 / +30
Video Input	
TV System	NTSC,SECAM,PAL,PAL-N,PAL-M,NTSC 4.43,PAL 60
Analogue video Signal	RGB,composite video,component video
Digital Video Standard	High-Definition Multimedia Interface (HDMI)
Video Interfaces	VGA,HDMI,composite video
Video Modes	480p,720p,1080i,1080p,480i,720i,526i,526p
LAN and Wireless Image Transferring Protocols	Wired LAN
Video Output	
Analogue Video Signal	RGB
Speakers	
Type	Integrated
Sound Output Mode	Mono
Output Power / Channel	10 Watt
Speaker(s)	1 x mixed channel
Input Device	
Type	External
Expansion / Connectivity	
Interfaces	1 x audio line-out - mini-phone stereo 3.5 mm 1 x RGB output - 15 pin HD D-Sub (HD-15) 2 x component video / RGB input - 15 pin HD D-Sub (HD-15) 1 x composite video input - RCA 2 x audio line-in - mini-phone stereo 3.5 mm 1 x USB 2.0 - 4 PIN USB Type B 1 x USB 2.0 - 4 PIN USB Type A

	1 x HDMI input - 19 pin HDMI Type A 1 x network - RJ-45 1 x serial RS-232C - 9 pin D-Sub (DB-9)
Miscellaneous	
Included Accessories	Wireless remote control
Cables Included	1 x VGA cable
Security Features	Security lock slot (cable lock sold separately),password protection,control panel lock,security bar
Power	
Nominal Voltage	AC 120/230 V (50/60 Hz)
Power Consumption Operational	298 Watt
Power Consumption Operational (Standby)	0.44 Watt
Software / System Requirements	
Software Included	Drivers & Utilities,EasyMP Network Projection,EasyMP Slide Converter,EasyMP Monitor,EasyMP Multi PC Projection
Dimensions & Weight	
Width	37.7 cm
Depth	10.8 cm
Height	27.1 cm
Weight	3.7 kg
Manufacturer Warranty	
Service & Support	3 years warranty
Service & Support Details	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80%
Sound Emission	37 dB
Sound Emission (Economic Mode)	29 dB

What's in the box

Epson EB 1930
Wireless remote control
VGA cable